

AC-3 ACOUSTIC CREATOR Specifications

Source guitars	16 types
Target guitars	15 types
Effect types	9 types
Sampling frequency	44.1 kHz
A/D conversion	24-bit 128 x oversampling
D/A conversion	24-bit 128 x oversampling
Signal processing	32-bit
Frequency characteristics	20 Hz-20 kHz (+1 dB/-3 dB) (10 kΩ load)
Input	Standard mono phone jack Rated input level: -20 dBu Input impedance: 10 MΩ
Outputs L/MONO/PHONES	Standard stereo phone jack (combined line/headphone) Maximum output level: Line +7 dBu (10 kΩ or more output impedance) Headphones 8 mW + 8 mW (32 Ω load)
R	Standard mono phone jack Maximum output level: Line +7 dBu (10 kΩ or more output impedance)
BALANCED OUT-L	XLR jack Output impedance: 100 Ω (HOT-GND, COLD-GND), 200 Ω (HOT-COLD) PRE/POST (switchable) GND LIFT (switchable)
BALANCED OUT-R	XLR jack Output impedance: 100 Ω (HOT-GND, COLD-GND), 200 Ω (HOT-COLD) GND LIFT (switchable)
S/N (equivalent input noise)	120 dBu
Noise floor (residual noise)	-100 dBu
Control input	FS01 Input
Power	AC adapter: 9V DC 500 mA center negative (ZOOM AD-16) Batteries: 2 AA (about 3 hours continuous operation time using alkaline batteries)
External dimensions	158 mm(D) X 237 mm(W) X 52 mm(H)
USB	USB MIDI USB Micro-B
Weight	1150 g(Not including batteries)
Options	FS01 foot switch

Note: 0 dBu = 0.775 V