

G5n Multi-Effects Processor Specifications

Effect types	128 types
Number of simultaneous effects	9
Number of user patches	200
Sampling frequency	44.1 kHz
A/D conversion	24-bit with 128x oversampling
D/A conversion	24-bit with 128x oversampling
Signal processing	32-bit
Frequency characteristics	20-20 kHz +1 dB, -3 dB (10 kΩ load)
Display	128x32 dot-matrix LCDs (4) 256x32 dot-matrix LCD
Input INPUT	Standard monaural phone jack Rated input level: -20 dBu Input impedance(line) : 470 kΩ
AUX IN	Stereo mini jack Rated input level: -10 dBu Input impedance(line) : 10 kΩ
Output (L/R)	Standard monaural phone jack x 2 Maximum output level: Line +5 dBu (with output load impedance of 10 kΩ or more)
Phone	Stereo mini jack Maximum output level: 20 mW + 20 mW (into 32 Ω load)
Equivalent input noise	-119 dBu
Noise floor (residual noise)	-101 dBu
Control input	For FP01/FP02
Power	AC adapter DC9V (center minus plug), 500 mA (ZOOM AD-16)
Dimensions	225 mm(D) X 454 mm(W) X 75 mm(H)
USB	USB Audio
Weight	3.4 kg
Options	FP01/FP02 expression pedal

• 0 dBu=0.775 V