

# MS-60B for Bass Specifications

---

NUMBER OF EFFECTS:	58
NUMBER OF SIMULTANEOUS EFFECTS:	4
NUMBER OF PATCH MEMORIES:	50
NUMBER OF PATCH PRESETS:	30
SAMPLING FREQUENCY:	44.1 kHz
A/D CONVERSION:	24-bit, 128 x oversampling
D/A CONVERSION:	24-bit, 128 x oversampling
SIGNAL PROCESSING:	32-bit floating point and 32-bit fixed point
FREQUENCY RESPONSE:	20Hz - 20 kHz +1 dB, -3 dB (into 10kΩ load)
DISPLAY:	LCD
INPUT:	1 x 1/4" monaural phone jack
RATED INPUT LEVEL:	-20 dBm*
INPUT IMPEDANCE:	1MΩ
OUTPUT:	2 x 1/4" monaural phone jack
MAXIMUM OUTPUT LEVEL:	+5 dBm (output impedance load of 10 kΩ or more)
BATTERY TYPE:	AA size (LR6) battery x 2
CONTINUOUS BATTERY OPERATION TIME:	7 hours when using 2 AA batteries
AC ADAPTER (OPTIONAL):	DC 9V center-negative, 500 mA (Zoom AD-16)
USB:	Firmware update, bus power
DIMENSIONS:	130.3 (D) x 77.5 (W) x 58.5 (H) mm
WEIGHT:	350g (without batteries)

\* Note: 0 dBm = 0.775 Vrms